






Rytons External Grilles

March 2010

Rytons Order/Specification Code	Main Uses, Features and Benefits	Size	Free Area	Colours
Code: CV60FBG 	Rytons RytAround Ventilator (Suits 100mm, 125mm & 150mm Range) Circular louvre grille with removable flyscreen. Suits tubes / holes 100mm to 150mm diameter. Fixed open inverted louvres allow high air flow. Slim profile with a flush finish. U.V. stabilised to protect against deterioration by sunlight.  Bar Coded and Bagged for Display	156mm Ext. Dia. x 13.5mm D	8900mm ² 89cm ² max. without flyscreen	WH, BR WH, BR flyscreen  U.V. stabilised
Code: RDLVBG 	Rytons '6x6' Louvre & 97mm Dia. Backplate (100mm Range) Low profile fixed open louvre grille with spigot for rigid pipe and flexible ducting. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight.  Bar Coded and Bagged for Display	166mm L x 160mm H x 97mm Dia. male spigot	7300mm ² 73cm ²	WH, TC, B/S, BL, BR WH backplate  U.V. stabilised
Code: RDFLVBG 	Rytons '6x6' Louvre with Flyscreen & 97mm Dia. Backplate (100mm Range) Low profile fixed open flyscreened louvre grille with spigot for rigid pipe and flexible ducting. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight.  Bar Coded and Bagged for Display	166mm L x 160mm H x 97mm Dia. male spigot	6423mm ² 64.23cm ²	WH, TC, B/S, BL, BR WH flyscreen and backplate  U.V. stabilised
Code: RD4GG 	Rytons Gravity Grille (100mm Range) Low profile gravity grille with spigot for rigid pipe and flexible ducting. Gravity flaps open when appliance is in operation. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Available Bar Coded and Bagged for Display - Code RD4GGBG	154mm L x 154mm H x 16mm D x 99mm Dia. male spigot	7200mm ² 72cm ²	WH, BR TC, B/S to order  U.V. stabilised
Code: RD4GSS 	Rytons Stainless Steel Gravity Grille (100mm Range) Low profile gravity grille with spigot for rigid pipe and flexible ducting. Gravity flaps open when appliance is in operation. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. Durable and stylish alternative to a plastic grille.	154mm L x 154mm H x 16mm D x 99mm Dia. male spigot	7000mm ² 70cm ²	Stainless Steel
Code: RD4CG 	Rytons Cowl Grille (100mm Range) External cowl grille with spigot for rigid pipe and flexible ducting. Gravity flap opens when appliance is in operation. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Available Bar Coded and Bagged for Display - Code RD4CGBG	154mm L x 154mm H x 78mm D x 99mm Dia. male spigot	7200mm ² 72cm ²	WH, BR TC, B/S to order  U.V. stabilised

Rytons External Grilles

March 2010

Rytons Order/Specification Code	Main Uses, Features and Benefits	Size	Free Area	Colours
Code: RD4CGSS 	Rytons Stainless Steel Cowled Grille (100mm Range) External cowl with spigot for rigid pipe and flexible ducting. Gravity flap opens when appliance is in operation. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. Durable and stylish alternative to a plastic grille.	154mm L x 154mm H x 78mm D x 99mm Dia. male spigot	7100mm ² 71cm ²	Stainless Steel
Code: RD4LGSS 	Rytons Stainless Steel Cowled Louvred Grille (100mm Range) Bull-nosed cowled vent with fixed open louvres and spigot for rigid pipe and flexible ducting. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. Durable and stylish alternative to a plastic grille.	99mm Dia. male spigot	4800mm ² 48cm ²	Stainless Steel
Code: RD4MGSS 	Rytons Stainless Steel Cowled Meshed Grille (100mm Range) Bull-nosed cowled vent with wire grille and spigot for rigid pipe and flexible ducting. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. Durable and stylish alternative to a plastic grille.	99mm Dia. male spigot	6300mm ² 63cm ²	Stainless Steel
Code: RD4LVGG 	Rytons Louvred/Gravity Grille (100mm Range) Low profile fixed open louvre grille with spigot for rigid pipe and flexible ducting. Easily converted to a gravity grille using flaps supplied. Connects to Rytons Rigid Pipe and suits 100mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Bar Coded and Bagged for Display	154mm L x 154mm H x 17mm D x 99mm Dia. male spigot	Not applicable 	WH, BR TC, B/S to order U.V. stabilised
Code: RD4AB/RD4ADAP 	Rytons Air Brick Grille featured with Rytons Flat Channel/Grille Adaptor (100mm Range) External grille-style air brick (RD4AB). Clips into Grille Adaptor (RD4ADAP) to connect to Rytons Rectangular RytHose and Flat Channel Ducting. U.V. stabilised to protect against deterioration by sunlight. Available Bar Coded and Bagged for Display	210mm L x 65mm H grille 108mm L x 50mm H x 20mm D adaptor	Not applicable 	Air Brick Grille: TC, B/S WH, BR to order Adaptor: WH U.V. stabilised
Code: RD5AB 	Rytons Air Brick Grille (125mm Range) External grille-style air brick with connector to Rytons Flat Channel Ducting. Suitable for use with Rytons Rectangular RytHose. U.V. stabilised to protect against deterioration by sunlight. Available Bar Coded and Bagged for Display - Code RD5ABBG	210mm L x 65mm H x 97mm D overall external	Not applicable 	TC, B/S U.V. stabilised

Rytons External Grilles

March 2010

Rytons Order/Specification Code	Main Uses, Features and Benefits	Size	Free Area	Colours
Code: RD5LVBG 	Rytons '6x6' Louvre & 122mm Dia. Backplate (125mm Range) Low profile fixed open louvre grille with spigot for rigid pipe and flexible ducting. Connects to Rytons Rigid Pipe and suits 125mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Bar Coded and Bagged for Display	166mm L x 160mm H x 122mm Dia. male spigot	10900mm ² 109cm ² 	WH, TC, B/S, BL, BR WH backplate U.V. stabilised
Code: RD5FLVBG 	Rytons '6x6' Louvre with Flyscreen & 122mm Dia. Backplate (125mm Range) Low profile fixed open flyscreened louvre grille with spigot for rigid pipe and flexible ducting. Connects to Rytons Rigid Pipe and suits 125mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Bar Coded and Bagged for Display	166mm L x 160mm H x 122mm Dia. male spigot	6423mm ² 64.23cm ² 	WH, TC, B/S, BL, BR WH flyscreen and backplate U.V. stabilised
Code: RD5GG 	Rytons Gravity Grille (125mm Range) Low profile gravity grille with spigot for rigid pipe and flexible ducting. Gravity flaps open when appliance is in operation. Connects to Rytons Rigid Pipe and suits 125mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Available Bar Coded and Bagged for Display - Code RD5GGBG	154mm L x 154mm H x 16mm D x 125mm Dia. male spigot	Not applicable 	WH, BR U.V. stabilised
Code: RD5CG 	Rytons Cowled Grille (125mm Range) External cowl with spigot for rigid pipe and flexible ducting. Gravity flap opens when appliance is in operation. Connects to Rytons Rigid Pipe and suits 125mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Available Bar Coded and Bagged for Display - Code RD5CGBG	154mm L x 154mm H x 78mm D x 125mm Dia. male spigot	Not applicable 	WH, BR U.V. stabilised
Code: RD6LVBG 	Rytons '7x7' Louvre & 144mm Dia. Backplate (150mm Range) Fixed open louvre grille with spigot for rigid pipe and flexible ducting. Connects to Rytons Rigid Pipe and suits 150mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Bar Coded and Bagged for Display	177mm L x 173mm H x 144mm Dia. male spigot	11995mm ² 119.95cm ² 	WH, TC, B/S WH backplate U.V. stabilised
Code: RD6GG 	Rytons Gravity Grille (150mm Range) Low profile gravity grille with spigot for rigid pipe and flexible ducting. Gravity flaps open when appliance is in operation. Connects to Rytons Rigid Pipe and suits 150mm dia. RytHose. U.V. stabilised to protect against deterioration by sunlight. Available Bar Coded and Bagged for Display - Code RD6GGBG	175mm L x 175mm H x 16mm D x 150mm Dia. male spigot	Not applicable 	WH, BR U.V. stabilised